



## 2013 AKA MANUAL

### ADDENDUM No. 18

Issued: 4<sup>th</sup> July, 2013

As per Postal Vote – PV2013-01, the NKC by majority vote have approved the changes to the following rules in the relevant Rotax Technical Specifications, effective immediately.

1. BRP-ROTAX FR 125 JUNIOR MAX TECHNICAL SPECIFICATIONS  
Rule 18.7  
No additional non-original cooling device is allowed. **For version 1, 2 and 3 tape can be applied around the radiator.** Tape may not be removed from the radiator during operation on the track. All other means of air flow control through the radiator are prohibited, **except for the plastic flap on version 3.** **For version 3, the removal of the original plastic flap and use of tape, like for version 1 and 2 of the radiator, is an acceptable configuration.**
  
2. BRP-ROTAX FR 125 MAX TECHNICAL SPECIFICATIONS  
Rule 18.7  
No additional non-original cooling device is allowed. **For version 1, 2 and 3 tape can be applied around the radiator.** Tape may not be removed from the radiator during operation on the track. All other means of air flow control through the radiator are prohibited, **except for the plastic flap on version 3.** **For version 3, the removal of the original plastic flap and use of tape, like for version 1 and 2 of the radiator, is an acceptable configuration.**
  
3. BRP-ROTAX FR 125 MAX DD2 TECHNICAL SPECIFICATIONS  
Rule 20.7  
No additional non-original cooling device is allowed. **For version 1 and 2, tape can be applied around the radiator.** Tape may not be removed from the radiator during operation on the track. All other means of air flow control through the radiator are prohibited, **except for the plastic flap on version 2.** **For version 2, the removal of the original plastic flap and use of tape, like for version 1 of the radiator, is an acceptable configuration.**

Pam Arnett  
National Secretary  
Australian Karting Association.